Issued date: 17/03/2023

Page 1 of 1

# SPECIFICATION SHEET

# **RENAISSANCE AVANTE™**

FOR OENOLOGICAL USE

Active dry yeast packaged in laminated foil under vacuum.

10476-01-99: 10 kg carton

10476-06-99: 20x500 g pack in a 10 kg carton

## **PHYSICAL PROPERTIES**

#### APPEARANCE & ODOUR

- · Form of round or vermiculated pellets
- Beige to light brown colour
- Typical yeast smell

#### **INGREDIENTS**

Active dry yeast Saccharomyces cerevisiae, E491.

# PRODUCT SPECIFICATIONS (in compliance with OIV Codex)

Viable yeast	> 10 <sup>10</sup> CFU/g
Dry matter	> 92 %
Coliform	< 10 <sup>2</sup> CFU/g
E. coli	Absent in 1 g
S. aureus	Absent in 1 g
Salmonella	Absent in 25 g
Lactic Acid Bacteria	< 10 <sup>5</sup> CFU/g
Acetic bacteria	< 10 <sup>4</sup> CFU/g
Moulds	< 10 <sup>3</sup> CFU/g
Yeast of different species	< 10 <sup>5</sup> CFU/g
Lead	
Mercury	< 1 mg/kg
Arsenic	
Cadmium	< 1 mg/kg

## **INSTRUCTIONS FOR USE**

Recommended dosage: 25-50 g/hL

- 1. Rehydrate the yeast in 10 times its weight in water (temperature between 35 °C and 40 °C).
- 2. Resuspend the yeast by gently stirring and wait for 20 minutes.
- 3. Mix the rehydrated yeast with a little juice/must, gradually adjusting the yeast suspension temperature to within 5-10 °C of the juice/must temperature.
- 4. Inoculate into the must.

<u>Notes:</u> The total rehydration time should not exceed 45 minutes. It is crucial that a clean container is used to rehydrate the yeast. Rehydration directly in must is generally not advisable. Ensure yeast nutrition is appropriately managed during fermentation.

# **STORAGE & SHELF LIFE**

Store in a dry and cool place.

4 years in original sealed packaging. Do not use active dry yeast if the packaging has lost its vacuum.

The information herein is based on current available data and is believed to be correct. No warranty, express or implied, is made regarding data accuracy, merchantability or hazards associated with product use. The user is responsible for determining product suitability, conditions of use and all associated hazards.